



U.S. COEXCELL OFFERS TWO ICAS PRODUCED TIGHT HEAD, ULTRA PURE DRUMS TO MEET YOUR SPECIFIC PARTICLE AND EXTRACTABLE REQUIREMENTS. MEET THE IC55UP AND C55UP!

EXCEPTIONAL DRUMS WITH SUPERIOR CHARACTERISTICS

- IC55UP and C55UP flange openings accept industry standard high purity extraction, gasket and O-ring styles used in ultra clean applications.
- IC55UP and C55UP drums, with dip-tubes, are certified for ultra clean integrity in U.S. COEXCELL's Class 100 liquid particle count test laboratory. Here we can provide purity certification to the lowest industry level.
- Three layer drum configuration isolates color concentrates and UV stabilizers in the outside layers of the IC55UP and C55UP drums.
- Virgin inner liner layer made with proprietary ultra clean resin assures chemical contact with pure HDPE only.
- UN tested and certified for transport of Group I, Group II and Group III chemistry with and without dip-tube.
- Patented drum design with integral sump below the flange for maximum extraction capability.



PATENTED AND EXCLUSIVE MOLD DESIGN PROMOTES SUPERIOR DRAINABILITY TO LESS THAN 50 ml.

WHY U.S. COEXCELL? CUTTING EDGE LEADERSHIP AND INNOVATION.

After nearly two decades, U.S. COEXCELL is recognized as the preminent innovator in producing uniquely engineered, multi-layer HDPE plastic molded drums. With the introduction of our proprietary ICAS technology we have taken our processes – and the purity of our drums – to a whole new level.

FOR MORE INFORMATION,
PLEASE CALL +1.419.897.9110

or write to us at:

U.S. COEXCELL

400 W. Dussel Drive

Maumee, Ohio 43537 USA

www.uscox.com



C55UP SPECIFICS

- Proven two piece drum design allows for inventory identification through multiple color combinations of drum body and handling ring.
- Two handling ring heights available for custom designed pump assembly and dip-tube protection.

Top Diameter	23.8" (60.5 cm)
Overall Height	(Std. profile) 36.5" (92.7 cm) (Tall profile) 38.25" (97.2 cm)
Overflow Capacity	60 gal. (227 liter)
Drum Body Weight	24 lbs. (10.9 kg)

IC55UP SPECIFICS

- One piece design delivers molded in handling capabilities
- Integral chime withstands heavier chemicals with a high specific gravity and elevated temperatures

Top Diameter	23.8" (60.5 cm)
Overall Height	35.75" (90.8 cm)
Overflow Capacity	58 gal. (220 liter)
Drum Body Weight	22 lbs. (10.0 kg)

THINKING INSIDE THE DRUM!

