



CONICAL PLASTIC N55 DRUMS: THE FOOD PROCESSOR'S TIME, SPACE AND MONEY SAVER!



DRUMS ARE PRODUCED IN ITALY FOR EASY DELIVERY THROUGHOUT EUROPE!

U.S.COEXCELL developed the N55 in collaboration with several leading members of the Florida citrus industry—people who are experts on the complexities of shipping and storage of food products. The result? A truly innovative container design that is re-shaping the way people do business.

The philosophy and products of U.S. COEXCELL offer a package that represents exceptional value to you and the customers you serve. You will find superior quality, outstanding performance, and a genuine concern for the environment in every U.S.COEXCELL N55 conical drum. Make a real difference in your company's bottom line.....

VALUE-ADDED BENEFITS:

- Open head drum constructed from virgin HDPE material that is certified for a wide variety of food grade applications such as frozen juice, tomato paste, fruit purees and brine vegetables.
- Body sidewall contains pigments and UV stabilizers to offer max. protection from the sun.
- Consistent drum, lid and lock band dimensions save time and labour.
- Plastic construction prevents corrosion or denting—outside storage no problem.
- Lighter weight - about half as heavy as steel drums, allowing for lighter transport loads.
- The conical shape allows empty drums to be nested allowing warehouse and transport efficiency to be improved by up to 75%!
- A long life cycle meaning N55 will outlast and get far more trips than their steel counterparts.
- Moulded in strapping channel allows proper restraint whilst the drum is on the pallet and during shipment.
- Designed to be easily handled with conventional drum handling equipment.

U.S.COEXCELL IS THE RIGHT CHOICE!

U.S. COEXCELL USA
400 W. Dussel Drive
Maumee, Ohio 43537
TEL: + 1 419 897 9110
FAX: + 1 419 897 9112

EUROPEAN SALES OFFICE:
Ruth Sutton
TEL: +44 77 33 55 44 44
EMAIL: rsutton@uscox.com
WEB: www.uscox.com



PRODUCT SPECIFICATIONS:

Body height:	95cm
Top diameter:	59.5cm
Base diameter:	49cm
De-nesting height:	19cm
Package height:	95.9cm
Min. Wall thickness:	0.29cm
Max Capacity:	208litres
Drum body weight:	7.3kg
Package weight:	8.65kg
Colour:	Black
(Other colours available upon special request.)	

FURTHER INFORMATION:

- Broad temperature operating range: -40°C to 60°C
Deflection point: 65°C to 71°C
Recommended stack height:
- Frozen - 3 high first 4 days thereafter 6 high
 - Aseptic with plastic USC pallets—3 high at fill temperature of -1°C to 27°C.

**ALLOW DRUMS TO COOL DOWN
BEFORE STACKING!**